

### **Filbag envelopes specification**

Based on information and declaration from the suppliers of foil declares that our foil envelopes produced in our factory are made of film containing minimum 80%recycled material.

The envelopes can be recycled after use.

Envelopes have been manufactured in accordance with PN-EN ISO 9001:2015, PN-EN ISO 14001:2015



### **Information on the optimum storage conditions for foil envelopes:**

- Foil envelopes should be protected from direct sunlight
- Foil envelopes should be stored in a dry area warehouse, the ideal temperature range is between 15° to 25°C
- Keep dry: ( relative humidity 45-70%)
- Keep appropriate distances from heating devices (1 m), from devices generating electromagnetic fields (10 m)

The period of guarantee is compatible with General Trading Conditions applied and with Conditions of Guarantee of foil envelopes only after compliance the storage conditions.

### Specification of basic stock items

Art. No.	Ref.	Description
<b>2FSDC260011</b>	<b>FB01</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 175 x 255 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 1000/ pallet 90.000 pcs
<b>2FSDC260012</b>	<b>FB02</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 225 x 325 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 1000/ pallet 45.000 pcs
<b>2FSDC260013</b>	<b>FB03</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 240 x 350 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 1000;/ pallet 45.000 pcs
<b>2FSDC260014</b>	<b>FB04</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 325 x 425 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 500 / pallet 27.000 pcs
<b>2FSDC260015</b>	<b>FB05</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 350 x 450 + 50 mm (+/-5 mm); ; Hot Melt glue + HDPE transparent silicone liner; box 500/pallet 27.000 pcs
<b>2FSDC260016</b>	<b>FB06</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 400 x 500 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 500/ pallet 18.000 pcs
<b>2FSDC260017</b>	<b>FB07</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 55 my +/- 5 my; dimensions 450 x 550 + 50 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 500 / pallet 18.000 pcs
<b>2FSDC260028</b>	<b>FBS08</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 65 my +/- 5my; dimensions 550 x 770 + 60 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 250 / pallet 8.000 pcs
<b>2FSDC260029</b>	<b>FBS09</b>	Foil Envelope ; Recycled co-extruded 3 layer white/black film; thickness 65 my +/- 5my; dimensions 600 x 900 + 70 mm (+/-5 mm); Hot Melt glue + HDPE transparent silicone liner; box 200/ pallet 6.400 pcs