



Via Caciagli 11 – Zona Industriale Terrafino 50053 Empoli
Tel 0571 930032 – 930065 fax 930056 viva@vivasrl.it

HAND CAST STRETCH FILM 23MIC

Topics	Results
1) Description:	Stretch film roll 50cm 23 micron
2) Raw material:	LLDPE Cast Stretch Wrap Film Polyethylene 23my Components : Paper core Rigid width 50mm
3) width roll:	50 cm \pm 1% (SP METHOD)
4) Film Length :	250mt \pm 8% (SP METHOD)
5) Color :	Natural Clear
6) Thickness :	23my \pm 1.5my (SP METHOD)
7) Density:	0.918 gr/cm ³ (ISO 1183 A METHOD)
8) Tensile strenght MD	55 Mpa (ASTM D882)
9) Tensile strenght TD	28 Mpa (ASTM D882)
10) Elongation at break %	150-180 % MD (SP METHOD)
11) Fusion point	121 C°
12) Impact strenght	110 gr (ASTM 1709)
11) Packing :	6 Bobine per cartone

Articolo : 1390

Marca: VIVA

Nome del Prodotto: Cast Stretch film

Product mechanical and physical properties are given by considering values of raw material supplier's product specification for 23 micron film at 25+ C° and 50% of humidity rate.

The values estimated are related to the samples analysed but can be different on the mass production.