



Sealed Air Limited
Product Care
Telford Way
Kettering,
Northamptonshire
NN16 8UN

Tel +44 1536 315700
Fax +44 1536 410576
www.sealedair-emea.com

Technical Data Sheet

Mail Lite Round Trip Mailers

COMPOSITION

Polyethylene coated paper laminated to a co-extruded plastic bubble film made from low-density polyethylene and plastic barrier A hot melt adhesive is added to the exposed paper to create a sealing lip. A backing paper is used to protect the adhesive from losing tacking properties until required. Second extra seal allowing outbound and inbound shipments. Standard Mail Lite are printed with Sealed Air logo, size identification and readable barcoding.

Paper is Chain of Custody (FSC) certified

Water-soluble inks are used for all printing designs.

PHYSICAL PROPERTIES

Type	Kraft white paper Dual Seal Bubble Mailer	
Mailer Size	D/1	LL
Mailers per carton	100	50
External Width	200mm +/- 8mm	250 +/- 8mm
Length excluding Lip	260mm +/- 8mm	330 +/- 8mm
Lip	70mm +10mm	75mm +10mm
Glue weight	0.1g - 0.05g	0.12g - 0.05g
Paper + PE layer	70g/m ² + 9g/m ² = total grammage 79 g/m ² - 6g/m ²	
AirCap bubble	30g/m ² +/- 2g/m ²	
Seam strength	15N +/- 5N	
Glue Strength	5N +/- 2N	

0210/17